

ELECTRIC PUMPS FOR LANDFILLS AND REMEDIATION SITES

SlimJim™ Pump Systems




Small diameter pump (4.5" OD)
provides flows up to 30 gpm in smaller risers
without the need of a control panel.

The Slim Jim is our small diameter, light weight and cost-effective Torpedo pump. No control panel is needed for this pump, with its built-in auto on/off start and run-dry protection. It offers plug-in operation at 115V or 230V single phase power. The rounded bullet end, heavy duty Torpedo™ shroud outperforms and outlasts stainless steel housings. There are no shroud wheels to break or hamper pump removal. The stainless steel motor and pump casing and HDPE protective shroud resist corrosion. There is also a chemical-resistant Teflon version.


The SlimJim pump is a great utility pump for general pit-vault dewatering, and excels in cleanouts, collapsed pipes or bent risers. The optional three phase operation with control panels adds several benefits: variable speed to program the pump with an iPhone (view and change pump data and parameters).

Specifications (See back for more details)

4.5" Environmental Pumps : 10, 22 gpm
4.5" Standard Pumps : 5,10,15, 22, 30 gpm



Flows up to 30 gpm
Delivers head capability to 330'. Consult website for flow curves of each model.



Lightweight
Compact, easy-to-handle
4.5" OD pump weighs only 22 pounds.



Cost Effective
Lowers capital costs and eases maintenance at over 500 landfills.



Plug-in Operation
Pump immediately using any 115V or 230V single phase power source.



SlimJim™ Pump Systems

SlimJim Environmental Pumps (Teflon and Viton seals)

		Flow (gpm)	Dia. (inches)	Length (lb)	Wt. HP	Volts	Phase	
50898	10SRPSJE05-100	10	4.5	34.4	22	½	115	Single
50899	10SRPSJE05-100	10	4.5	34.4	22	½	230	Single
50900	10SRPSJE05-140	10	4.5	34.4	22	½	115	Single
50901	10SRPSJE05-140	10	4.5	34.4	22	½	230	Single
50902	10SRPSJE07-180	10	4.5	35.5	23	¾	230	Single
50903	10SRPSJE07-220	10	4.5	37.6	23	¾	230	Single
50904	10SRPSJE10-260	10	4.5	39.0	26	1	230	Single
50905	10SRPSJE10-300	10	4.5	40.1	26	1	230	Single
50906	10SRPSJE10-340	10	4.5	42.2	26	1	230	Single
50907	22SRPSJE05-40	22	4.5	34.4	22	½	115	Single
50908	22SRPSJE05-40	22	4.5	34.4	22	½	230	Single
50909	22SRPSJE05-80	22	4.5	34.4	22	½	115	Single
50910	22SRPSJE05-80	22	4.5	34.4	22	½	230	Single
50911	22SRPSJE07-110	22	4.5	35.5	23	¾	230	Single
50912	22SRPSJE05-140	22	4.5	37.6	23	½	230	Single
50913	22SRPSJE10-180	22	4.5	42.2	26	1	230	Single
50914	22SRPSJE10-210	22	4.5	42.2	26	1	230	Single

SlimJim Standard Pumps (Buna Seals)

50915	5SRPSJ05-90	5	4.5	34.4	22	½	115	Single
50916	5SRPSJ05-90	5	4.5	34.4	22	½	230	Single
50917	5SRPSJ05-140	5	4.5	34.4	22	½	115	Single
50918	5SRPSJ05-140	5	4.5	34.4	22	½	230	Single
50919	5SRPSJ05-180	5	4.5	35.5	22	½	115	Single
50920	5SRPSJ05-180	5	4.5	35.5	22	½	230	Single
50921	5SRPSJ07-230	5	4.5	37.6	23	¾	230	Single
50922	5SRPSJ07-270	5	4.5	37.6	23	¾	230	Single
50923	5SRPSJ07-320	5	4.5	38.6	23	¾	230	Single
50924	5SRPSJ10-360	5	4.5	42.2	26	1	230	Single
50925	5SRPSJ10-410	5	4.5	42.2	26	1	230	Single
50926	5SRPSJ15-450	5	4.5	43.3	26	1½	230	Single
50927	10SRPSJ05-110	10	4.5	34.4	22	½	115	Single
50928	10SRPSJ05-110	10	4.5	34.4	22	½	230	Single
50929	10SRPSJ05-160	10	4.5	34.4	22	½	230	Single
50930	10SRPSJ07-200	10	4.5	35.5	23	¾	230	Single
50931	10SRPSJ07-260	10	4.5	37.6	23	¾	230	Single
50932	10SRPSJ10-290	10	4.5	39.0	26	1	230	Single
50933	10SRPSJ15-330	10	4.5	40.2	26	1½	230	Single
50934	15SRPSJ05-70	15	4.5	34.4	22	½	115	Single
50935	15SRPSJ05-70	15	4.5	34.4	22	½	230	Single
50936	15SRPSJ05-110	15	4.5	34.4	22	½	115	Single
50937	15SRPSJ05-110	15	4.5	34.4	22	½	230	Single
50938	15SRPSJ07-150	15	4.5	35.5	23	¾	230	Single
50939	15SRPSJ07-180	15	4.5	37.6	23	¾	230	Single
50940	15SRPSJ10-220	15	4.5	39.0	26	1	230	Single
50941	15SRPSJ10-250	15	4.5	40.1	26	1	230	Single
50942	15SRPSJ15-290	15	4.5	42.2	26	1½	230	Single
50943	22SRPSJ05-40	22	4.5	34.4	22	½	115	Single
50944	22SRPSJ05-40	22	4.5	34.4	22	½	230	Single
50945	22SRPSJ05-80	22	4.5	34.4	22	½	115	Single
50946	22SRPSJ05-80	22	4.5	34.4	23	½	230	Single
50947	22SRPSJ07-120	22	4.5	35.5	23	¾	230	Single
50948	22SRPSJ10-160	22	4.5	37.6	23	1	230	Single
50949	22SRPSJ10-190	22	4.5	42.2	26	1	230	Single
50950	22SRPSJ15-220	22	4.5	42.2	26	1½	230	Single
50951	30SRPSJ05-40	30	4.5	34.4	22	½	115	Single
50952	30SRPSJ05-40	30	4.5	34.4	22	½	230	Single
50953	30SRPSJ07-90	30	4.5	34.4	23	¾	230	Single
50954	30SRPSJ10-130	30	4.5	39.0	23	1	230	Single

Accessories



Commander™ Control Panels Touch Screen Standard

- Touch screen displays
- Adjust alarm, transducer flow meter setup
- Breakers, not fuses.
- Isolation barriers.
- "Finger-safe" safety standards.
- 304 Stainless Steel Enclosure.



Level Transducers

- High static accuracy and repeatability
- Ranges from 3-1000 PSI gauge
- Easy field maintenance



Flow Meters

- Traditional insertion & magnetic meters
- Low-voltage solar powered option

For complete details on all
products visit:
www.qedenv.com



Innovative Environmental Products